


K-SPIR SCHL KUPPL SET

Spiral hose and coupling kits

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Ekspluatācijas spiediens
max. 10 bar (to the temperature +20 °C); max. 7 bar (at temperature +40 °C); max. 5 bar
(at temperature +60 °C)
Spirālveida šļūtene
Polyurethane

Apraksts

For pneumatic applications in challenging industrial environments. High-quality, one-hand quick disconnect coupling made of steel with safety lock to prevent unintentional disconnection. For complex applications susceptible to severe mechanical wear. The outer layer of the hose, which is designed to withstand flying sparks and scorching, has special spark protection. It is therefore ideal for all pneumatic tools used in welding processes.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Šļūtenes izmērs | Ø spirālei mm | Darba garums m |
|----------------|-----------------|------------------|-------------------|
| K- 07 10 07 56 | 10 mm x 6,5 mm | 52 | 4.0 |
| K- 07 10 07 57 | 10 mm x 6,5 mm | 52 | 6.0 |
| K- 07 10 07 58 | 12 mm x 8 mm | 65 | 8.0 |