

# K-SPIR SCHL KUPPL SET LKM

## NW 7,6

Spiral hose and coupling kits, with safety couplings DN 7.6



Ekspluatācijas spiediens  
10 bar  
Vielas temperatūra  
-20 °C to +60 °C

## Apraksts

Couplings: High-grade single-handed quick-release coupling and safety coupling in steel / brass zinc-plated for high flow rates, specially designed for all applications with high mechanical wear. Strong, impact- and vibration-resistant construction for challenging applications. Polyurethane hose  
Exceedingly flexible, extremely kink-resistant and tolerant of dirt spiral hose with high resilience under tear, tensile and impact loads with a long service life and outstanding ageing qualities. It is also UV resistant and has outstanding abrasion resistance.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Šļūtenes izmērs	Ø spirālei mm	Darba garums m
K- 07 10 07 65	10 mm x 6,5 mm	52	2.0
K- 07 10 07 66	10 mm x 6,5 mm	52	4.0
K- 07 10 07 67	10 mm x 6,5 mm	52	6.0
K- 07 10 07 68	10 mm x 6,5 mm	52	8.0
K- 07 10 07 69	12 mm x 8 mm	65	2.0
K- 07 10 07 70	12 mm x 8 mm	65	4.0
K- 07 10 07 71	12 mm x 8 mm	65	6.0
K- 07 10 07 72	12 mm x 8 mm	65	8.0