

# K-RD DURCHGANGSFORM LEI VA

Check valve - straight-way type, lightweight series, stainless steel



Ekspluatācijas spiediens  
2 - 16 bar  
Ekspluatācijas temperatūra  
-20 °C to +150 °C  
Atspere  
Stainless steel 1.4301  
Blīvējums  
FKM  
Korpuss  
Stainless steel 1.4301  
Sākotnējais spiediens  
min. 0.03 bar

## Apraksts

Stainless steel check valve with full bore and very low opening pressure, no maintenance required. Applications: Compressed air, water, neutral gases, gaseous and liquid non-corrosive media, oils.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	A mm	C mm	L mm
K- 07 30 29 23	G 1/4	20.0	32.0	55.9
K- 07 30 29 28	G 3/8	20.0	32.0	56.0
K- 07 30 29 22	G 1/2	25.0	32.0	55.6
K- 07 30 29 27	G 3/4	29.0	44.0	66.7
K- 07 30 29 19	G 1	36.0	53.0	83.6
K- 07 30 29 21	G 1 1/4	45.0	62.0	96.0
K- 07 30 29 20	G 1 1/2	51.0	78.0	114.0
K- 07 30 29 24	G 2	64.0	89.0	120.5
K- 07 30 29 25	G 2 1/2	80.0	113.0	141.5
K- 07 30 29 26	G 3	94.0	132.0	160.0