

K-RD DURCHGANGSFORM LEI VA

Check valve - straight-way type, lightweight series, stainless steel



Ekspluatācijas spiediens
2 - 16 bar
Ekspluatācijas temperatūra
-20 °C to +150 °C
Atspere
Stainless steel 1.4301
Blīvējums
FKM
Korpuss
Stainless steel 1.4301
Sākotnējais spiediens
min. 0.03 bar

Apraksts

Stainless steel check valve with full bore and very low opening pressure, no maintenance required. Applications: Compressed air, water, neutral gases, gaseous and liquid non-corrosive media, oils.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	A mm	C mm	L mm
K- 07 30 29 23	G 1/4	20.0	32.0	55.9
K- 07 30 29 28	G 3/8	20.0	32.0	56.0
K- 07 30 29 22	G 1/2	25.0	32.0	55.6
K- 07 30 29 27	G 3/4	29.0	44.0	66.7
K- 07 30 29 19	G 1	36.0	53.0	83.6
K- 07 30 29 21	G 1 1/4	45.0	62.0	96.0
K- 07 30 29 20	G 1 1/2	51.0	78.0	114.0
K- 07 30 29 24	G 2	64.0	89.0	120.5
K- 07 30 29 25	G 2 1/2	80.0	113.0	141.5
K- 07 30 29 26	G 3	94.0	132.0	160.0