

K-WV 3/2 5/2 5/3 HAND

3/2, 5/2 and 5/3-way pilot valves



Ekspluatācijas spiediens
2.5 - 10 bar (monostable)
1.0 - 10 bar (bistable)
Max. vacuum 10 bar
Temperatūras diapazons
-10 °C to +60 °C
Caurplūde 6 bar un 5 bar
400 NL/min (G 1/8), 750 NL/min (G 1/4), 1560 NL/min (G 3/8), 3200 NL/min (G 1/2)
Caurplūde 6 bar un 10 bar
550 NL/min (G 1/8), 1100 NL/min (G 1/4), 2150 NL/min (G 3/8), 4600 NL/min (G 1/2)
Vārsta korpusa
Alumīnijs
Atspere
Special steel
Virzulis
Nickel-plated aluminium
Blīvējums
NBR

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Savienojums | Funkcija | Slēguma shēmas numurs | Vadība |
|----------------|-------------|----------|-----------------------|------------|
| K- 07 15 00 70 | G 1/8" | 3/2-way | 10 | Monostabil |
| K- 07 15 00 71 | G 1/8" | 3/2-way | 11 | Bistabil |
| K- 07 15 00 72 | G 1/4" | 3/2-way | 10 | Monostabil |
| K- 07 15 00 73 | G 1/4" | 3/2-way | 11 | Bistabil |
| K- 07 15 00 74 | G 1/2" | 3/2-way | 10 | Monostabil |
| K- 07 15 00 75 | G 1/2" | 3/2-way | 11 | Bistabil |
| K- 07 15 02 29 | G 1/8" | 5/2-way | 12 | Monostabil |
| K- 07 15 02 30 | G 1/8" | 5/2-way | 13 | Bistabil |
| K- 07 15 02 31 | G 1/4" | 5/2-way | 12 | Monostabil |
| K- 07 15 02 32 | G 1/4" | 5/2-way | 13 | Bistabil |
| K- 07 15 02 33 | G 1/2" | 5/2-way | 12 | Monostabil |
| K- 07 15 02 34 | G 1/2" | 5/2-way | 13 | Bistabil |
| K- 07 15 03 57 | G 1/8" | 5/3-way | 14 | Monostabil |
| K- 07 15 03 58 | G 1/8" | 5/3-way | 15 | Bistabil |
| K- 07 15 03 59 | G 1/8" | 5/3-way | 16 | Monostabil |
| K- 07 15 03 60 | G 1/8" | 5/3-way | 17 | - |
| K- 07 15 03 61 | G 1/8" | 5/3-way | 18 | - |
| K- 07 15 03 62 | G 1/8" | 5/3-way | 19 | - |
| K- 07 15 03 63 | G 1/4" | 5/3-way | 14 | Monostabil |
| K- 07 15 03 64 | G 1/4" | 5/3-way | 15 | Bistabil |
| K- 07 15 03 65 | G 1/4" | 5/3-way | 16 | Monostabil |
| K- 07 15 03 66 | G 1/4" | 5/3-way | 17 | - |
| K- 07 15 03 67 | G 1/4" | 5/3-way | 18 | - |
| K- 07 15 03 68 | G 1/4" | 5/3-way | 19 | - |
| K- 07 15 03 69 | G 1/2" | 5/3-way | 14 | Monostabil |
| K- 07 15 03 70 | G 1/2" | 5/3-way | 15 | Bistabil |
| K- 07 15 03 71 | G 1/2" | 5/3-way | 16 | Monostabil |
| K- 07 15 03 72 | G 1/2" | 5/3-way | 17 | - |
| K- 07 15 03 73 | G 1/2" | 5/3-way | 18 | - |
| K- 07 15 03 74 | G 1/2" | 5/3-way | 19 | - |