



Ekspluatācijas spiediens
2,5 - 10 bar (monostable)
1,0 - 10 bar (bistable)
vacuum up to 10 bar (external pilot air)
min. darba spiediens
2.5 bar (monostable), 1.0 bar (bistable)
Temperatūras diapazons
-10 °C to +60 °C
Caurplūde 6 bar un 5 bar
400 NL/min (G 1/8), 750 NL/min (G 1/4), 1560 NL/min (G 3/8), 3200 NL/min (G 1/2)
Caurplūde 6 bar un 10 bar
550 NL/min (G 1/8), 1100 NL/min (G 1/4), 2150 NL/min (G 3/8), 4600 NL/min (G 1/2)

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Savienojums	Spriegums	DN	Funkcija	Slēguma shēmas numurs	Vadība
K- 07 15 00 23	G 1/8"	24 V DC	5	3/-way NO	32	Monostabil
K- 07 15 00 24	G 1/4"	24 V DC	8	3/-way NO	32	Monostabil
K- 07 15 25 75	G 3/8"	24 V DC	13	3/-way NO	32	Monostabil
K- 07 15 00 25	G 1/2"	24 V DC	15	3/-way NO	32	Monostabil
K- 07 15 00 26	G 1/8"	230 V, 50 Hz	5	3/-way NO	32	Monostabil
K- 07 15 00 27	G 1/4"	230 V, 50 Hz	8	3/-way NO	32	Monostabil
K- 07 15 25 76	G 3/8"	230 V, 50 Hz	13	3/-way NO	32	Monostabil
K- 07 15 00 28	G 1/2"	230 V, 50 Hz	15	3/-way NO	32	Monostabil
K- 07 15 00 29	G 1/8"	24 V DC	5	3/2-way NC	33	Monostabil
K- 07 15 00 30	G 1/4"	24 V DC	8	3/2-way NC	33	Monostabil
K- 07 15 25 77	G 3/8"	24 V DC	13	3/2-way NC	33	Monostabil
K- 07 15 00 31	G 1/2"	24 V DC	15	3/2-way NC	33	Monostabil
K- 07 15 00 32	G 1/8"	230 V, 50 Hz	5	3/2-way NC	33	Monostabil
K- 07 15 00 33	G 1/4"	230 V, 50 Hz	8	3/2-way NC	33	Monostabil
K- 07 15 25 78	G 3/8"	230 V, 50 Hz	13	3/2-way NC	33	Monostabil
K- 07 15 00 34	G 1/2"	230 V, 50 Hz	15	3/2-way NC	33	Monostabil
K- 07 15 00 35	G 1/8"	24 V DC	5	3/2-way	34	Bistabil
K- 07 15 00 36	G 1/4"	24 V DC	8	3/2-way	34	Bistabil
K- 07 15 25 79	G 3/8"	24 V DC	13	3/2-way	34	Bistabil
K- 07 15 00 37	G 1/2"	24 V DC	15	3/2-way	34	Bistabil
K- 07 15 00 38	G 1/8"	230 V, 50 Hz	5	3/2-way	34	Bistabil
K- 07 15 00 39	G 1/4"	230 V, 50 Hz	8	3/2-way	34	Bistabil
K- 07 15 25 80	G 3/8"	230 V, 50 Hz	13	3/2-way	34	Bistabil
K- 07 15 00 40	G 1/2"	230 V, 50 Hz	15	3/2-way	34	Bistabil