

# K-WV 5/2 DIFFERENZIALKOLBEN

5/2-way pilot valves, with differential piston



Ekspluatācijas spiediens  
2,5 - 10 bar (monostable)  
1,0 - 10 bar (bistable)  
vacuum up to 10 bar (external pilot air)  
min. darba spiediens  
2.5 bar (monostable), 1.0 bar (bistable)  
Temperatūras diapazons  
-10 °C to +60 °C  
Caurplūde 6 bar un 5 bar  
400 NL/min (G 1/8), 750 NL/min (G 1/4), 1560 NL/min (G 3/8), 3200 NL/min (G 1/2)  
Caurplūde 6 bar un 10 bar  
550 NL/min (G 1/8), 1100 NL/min (G 1/4), 2150 NL/min (G 3/8), 4600 NL/min (G 1/2)

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Savienojums	Spriegums	DN	Funkcija	Slēguma shēmas numurs	Vadība
K- 07 15 02 05	G 1/8"	24 V DC	5	5/2-way	36	Bistabil
K- 07 15 02 06	G 1/4"	24 V DC	8	5/2-way	36	Bistabil
K- 07 15 25 85	G 3/8"	24 V DC	13	5/2-way	36	Bistabil
K- 07 15 02 07	G 1/2"	24 V DC	15	5/2-way	36	Bistabil
K- 07 15 02 08	G 1/8"	230 V, 50 Hz	5	5/2-way	36	Bistabil
K- 07 15 02 09	G 1/4"	230 V, 50 Hz	8	5/2-way	36	Bistabil
K- 07 15 25 86	G 3/8"	230 V, 50 Hz	13	5/2-way	36	Bistabil
K- 07 15 02 10	G 1/2"	230 V, 50 Hz	15	5/2-way	36	Bistabil