

# K-WV 5/3 MITTELSTELLUNSVENT

5/3-way pilot valves (monostable)



Funkcija

5/3-way

Eksploatācijas spiediens

Max. vacuum 10 bar

min. darba spiediens

1,0 bar (bistabil)

Temperatūras diapazons

-10 °C to +60 °C

Caurplūde 6 bar un 5 bar

400 NL/min (G 1/8), 750 NL/min (G 1/4), 1560 NL/min (G 3/8), 3200 NL/min (G 1/2)

Caurplūde 6 bar un 10 bar

550 NL/min (G 1/8), 1100 NL/min (G 1/4), 2150 NL/min (G 3/8), 4600 NL/min (G 1/2)

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Savienojums	DN	Funkcija	Slēguma shēmas numurs
K- 07 15 03 48	G 1/8"	5	5/3-way	29
K- 07 15 03 49	G 1/8"	5	5/3-way	30
K- 07 15 03 50	G 1/8"	5	5/3-way	31
K- 07 15 03 51	G 1/4"	8	5/3-way	29
K- 07 15 03 52	G 1/4"	8	5/3-way	30
K- 07 15 03 53	G 1/4"	8	5/3-way	31
K- 07 15 25 72	G 3/8"	13	5/3-way	29
K- 07 15 25 73	G 3/8"	13	5/3-way	30
K- 07 15 25 74	G 3/8"	13	5/3-way	31
K- 07 15 03 54	G 1/2"	15	5/3-way	29
K- 07 15 03 55	G 1/2"	15	5/3-way	30
K- 07 15 03 56	G 1/2"	15	5/3-way	31