


Pressure indicators, thread (input) - pipe (output)



Eksploatācijas spiediens

2 - 10 bar

Temperatūras diapazons

-20 °C to +60 °C

Korpuss

Technopolymer

Iekšējās daļas

nickel-plated brass, brass, &amp;lt;br&amp;gt;technopolymer, stainless steel

Blīvējums

NBR

Montāža

Wall mounting (housing with drilled holes)

Bracket mounting (mounting bracket available)

Panel mounting (with bracket or lock nut)

Simbols

on the housing

## Apraksts

A carefully selected assortment of products for installation in pneumatic circuits. These small, highly efficient components allow all pneumatic functions to be implemented anywhere in the circuit. The series has an ultramodular design. &lt;br&gt;All components can be installed In parallel, In series, In a mixed parallel / serial configuration. Available as Pipe / pipe connection with two plug connectors Thread / pipe connection, with one plug connector and one nickel-plated brass thread.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vitnes	šļūtenes Ø mm	A mm	B mm	I mm
K- 07 15 05 79	G 1/8	6	58.5	37.0	14.6
K- 07 15 05 80	G 1/8	8	66.2	41.0	18.7
K- 07 15 05 77	G 1/4	6	61.5	37.0	14.6
K- 07 15 05 78	G 1/4	8	70.6	41.0	18.7
K- 07 15 05 81	G 3/8	8	72.2	41.0	18.7