


Pressure regulators, pipe (input) - thread (output)



Ekspluatācijas spiediens
2 - 10 bar
Caurplūde 6,3 bar
400 NL/min (Ø 6 and G 1/8), 600 NL/min (Ø 8 and G 1/4)
Temperatūras diapazons
-20 °C to +60 °C
Korpuss
Technopolymer
Iekšējās daļas
nickel-plated brass, brass,
technopolymer, stainless steel
Blīvējums
NBR
Montāža
Wall mounting (housing with drilled holes)
Bracket mounting (mounting bracket available)
Panel mounting (with bracket or lock nut)
Simbols
on the housing

Apraksts

A carefully selected assortment of products for installation in pneumatic circuits. These small, highly efficient components allow all pneumatic functions to be implemented anywhere in the circuit. The series has an ultramodular design.
All components can be installed In parallel, In series, In a mixed parallel / serial configuration. Available as Pipe / pipe connection with two plug connectors Thread / pipe connection, with one plug connector and one nickel-plated brass thread.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Vītnes | Šļūtenes Ø mm | Regulēšanas diapazons | A mm | B mm | I mm |
|----------------|--------|------------------|-----------------------|---------|---------|---------|
| K- 07 25 03 19 | G 1/8 | 6 | 1 - 8 bar | 58.5 | 52.0 | 14.6 |
| K- 07 25 03 20 | G 1/8 | 8 | 1 - 8 bar | 61.5 | 52.0 | 14.6 |
| K- 07 25 03 17 | G 1/4 | 6 | 1 - 8 bar | 66.2 | 58.0 | 18.7 |
| K- 07 25 03 18 | G 1/4 | 8 | 1 - 8 bar | 70.6 | 58.0 | 18.7 |
| K- 07 25 03 21 | G 3/8 | 8 | 1 - 8 bar | 72.2 | 58.0 | 18.7 |