

K-SNV ENTLUE V SCHL SCHL

Quick-exhaust valves, conveyed exhaust, pipe - pipe



Ekspluatācijas spiediens

1 - 10 bar

Caurplūde 6,3 bar

50 NL/min (Ø 4), 270 NL/min (Ø 6), 400 NL/min (Ø 8)

Caurplūde Atgaisošana 6,3 bar

100 NL/min (Ø 4), 700 NL/min (Ø 6), 1000 NL/min (Ø 8)

Temperatūras diapazons

-20 °C to +60 °C

Korpuss

Technopolymer

Iekšējās daļas

nickel-plated brass, brass,
technopolymer, stainless steel

Blīvējums

NBR

Montāža

Wall mounting (housing with drilled holes)

Bracket mounting (mounting bracket available)

Panel mounting (with bracket or lock nut)

Simbols

on the housing

Apraksts

A carefully selected assortment of products for installation in pneumatic circuits. These small, highly efficient components allow all pneumatic functions to be implemented anywhere in the circuit. The series has an ultramodular design.
All components can be installed In parallel, In series, In a mixed parallel / serial configuration. Available as Pipe / pipe connection with two plug connectors Thread / pipe connection, with one plug connector and one nickel-plated brass thread.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Šļūtenes Ø mm	A mm	B mm	I mm
K- 07 15 25 27	4	41.8	25.8	12.8
K- 07 15 20 30	6	49.0	30.2	14.6
K- 07 15 20 31	8	57.2	35.9	18.7