

# K-DRV ABLD GEW C RAENDEL

**HANSA FLEX**

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Unidirectional flow control valves, outgoing air restriction (»C«), screw connection



Ekspluatācijas spiediens  
maks. 10 bar  
Temperatūras diapazons  
0 °C to +70 °C  
Dobskrūve, pagriežama svira, regulēšanas skrūve  
Nickel-plated brass  
Iekšējās daļas  
Brass with a bare metal surface  
Blīvgredzena apmales blīvējums  
NBR  
Blīvējumi (nepazaudējami)  
Polyamide (glass fibre-reinforced)

## Apraksts

For fine regulation of a cylinder piston speed and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	C mm	Savienojums	SW	Vītnes	B mm
K- 07 15 04 57	11.5	M 5 female	8 mm	M 5	38.9
K- 07 15 04 62	16.0	G 1/8 female	14 mm	G 1/8	42.0
K- 07 15 04 58	22.0	G 1/4 female	17 mm	G 1/4	51.0
K- 07 15 25 14	32.0	G 1/2 female	26 mm	G 1/2	81.0
K- 07 15 25 15	26.0	G 3/8 female	20 mm	G 3/8	63.0