

K-DRV GEW V RAENDEL

Unidirectional flow control valves, incoming air restriction (»V«), screw connection



Ekspluatācijas spiediens
maks. 10 bar
Temperatūras diapazons
0 °C to +70 °C
Dobskrūve, pagriežama svira, regulēšanas skrūve
Nickel-plated brass
Iekšējās daļas
Brass with a bare metal surface
Blīvgredzena apmales blīvējums
NBR
Blīvējumi (nepazaudējami)
Polyamide (glass fibre-reinforced)

Apraksts

For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder. Compact type of construction, also ideal where space is restricted. On the version with a knurled screw, the set volumetric flow rate can be locked with the hexagon nut to obtain a fixed setting.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	C mm	Savienojums	SW	Vītnes	B mm
K- 07 15 25 19	11.5	M 5 female	8 mm	M 5	38.9
K- 07 15 05 17	16.0	G 1/8 female	14 mm	G 1/8	42.4
K- 07 15 05 13	22.0	G 1/4 female	17 mm	G 1/4	51.0
K- 07 15 25 20	26.0	G 3/8 female	20 mm	G 3/8	63.0