

# K-DRV GEW V SCHLITZ

Unidirectional flow control valves, incoming air restriction (»V«), screw connection



Ekspluatācijas spiediens  
maks. 10 bar  
Temperatūras diapazons  
0 °C to +70 °C  
Dobskrūve, pagriežama svira, regulēšanas skrūve  
Nickel-plated brass  
Iekšējās daļas  
Brass with a bare metal surface  
Blīvgredzena apmales blīvējums  
NBR  
Blīvējumi (nepazaudējami)  
Polyamide (glass fibre-reinforced)

## Apraksts

For fine regulation of a cylinder piston speed in the forward and return motion and precise control of flow rates. Designed as a banjo-type valve with a hollow bolt and ring piece. Can be screwed directly onto the valve or cylinder to restrict the incoming air. Compact type of construction, also ideal where space is restricted.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	C mm	Savienojums	SW	Vītnes	B mm
K- 07 15 25 21	11.5	M 5 female	8 mm	M 5	24.5
K- 07 15 05 70	16.0	G 1/8 female	14 mm	G 1/8	32.0
K- 07 15 05 66	22.0	G 1/4 female	17 mm	G 1/4	40.0
K- 07 15 25 22	26.0	G 3/8 female	20 mm	G 3/8	50.0