

# K-STOPPVENTILE IG

Stop valves, ports 2 and 3 with female thread

**HANSA FLEX**

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba spiediens  
Max. 10 bar  
Regulēšanas spiediens  
1 - 5 bar, depending on operating pressure  
Vielas temperatūra  
max. 70 °C  
Uzstādīšanas stāvoklis  
Any. Ring pieces can still be rotated 360° after the valve has been tightened  
Materiāls  
Niķelēts misiņš  
Blīvējums  
Perbunan

## Apraksts

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Port 1	Port 2	Savienojums 3	B mm	C mm
K- 07 15 20 46	G 1/8"	G 1/8"	G 1/8"	52.0	21.0
K- 07 15 20 45	G 1/4"	G 1/4"	G 1/8"	58.0	25.0
K- 07 15 20 47	G 3/8"	G 3/8"	G 1/8"	63.0	31.0
K- 07 15 20 44	G 1/2"	G 1/2"	G 1/8"	72.0	40.0