

K-STOPPVENTILE STECK

Stop valves, ports 2 and 3 with plug connection



Darba spiediens

Max. 10 bar

Regulēšanas spiediens

1 - 5 bar, depending on operating pressure

Vielas temperatūra

max. 70 °C

Uzstādīšanas stāvoklis

Any. Ring pieces can still be rotated 360° after the valve has been tightened

Blīvējums

Perbunan

Apraksts

For high-speed positioning and stop functions as well as emergency switching (e.g. emergency stop). If a control signal is present at port 3, air can flow to and from the cylinder. If no control signal is present, the air flow to and from the cylinder is shut off, causing the cylinder to stop in the required position. Stop valves are screwed directly onto the cylinder instead of the normal pipe connections.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Materiāls	Port 1	Port 2	Savienojums 3	B mm	C mm
K- 07 15 20 50	Niķelēts misiņš	G 1/8"	6 mm	4 mm	52.0	25.0
K- 07 15 20 49	Niķelēts misiņš	G 1/4"	6 mm	4 mm	58.0	28.0
K- 07 15 20 51	Niķelēts misiņš	G 3/8"	8 mm	4 mm	63.0	32.0
K- 07 15 20 48	Niķelēts misiņš	G 1/2"	12 mm	4 mm	72.0	41.0