


# K-MV G D 24 V DC

Normally closed, directly operated, 24 V DC (direct current)



Aizsardzības veids  
IP65 (with connector socket fitted)  
Elektriskais pieslēgums  
ISO 4400. cable socket (Pg 11P)  
Vielas temperatūra  
max. +80 °C with Perbunan-seal; max. +130 °C with FKM-Seal  
Vītnes apraksts  
G-thread acc. to DIN EN ISO 228-1, Rp-thread acc. to ISO 7-1  
Iekšējās daļas  
Stainless steel  
Korpuss, vārsta ligzda  
Brass  
Blīvējums  
Perbunan (NBR) or FKM

## Apraksts

Standard series, proven over many years, available in three different versions: Directly operated, Combined operation, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	maks. darba spiediens bar	NW	Blīvēšanas materiāls	A mm	B mm	Konstrukcija
K- 07 30 23 08	G 1/8	5	03	NBR	75.0	30.0	1
K- 07 30 23 10	G 1/8	5	03	FKM	75.0	30.0	1
K- 07 30 23 09	G 1/4	4	03	NBR	75.0	40.0	2
K- 07 30 23 11	G 1/4	4	03	FKM	75.0	40.0	2