

K-MV 0 D 230 V, 50 - 60

HZ

Normally open, directly operated, 230 V, 50 to 60 Hz



Aizsardzības veids
IP65 (with connector socket fitted)
Elektriskais pieslēgums
For connector socket Pg 9/Pg 11, acc. to ISO 4400
Vielas temperatūra
-10 °C to +90 °C (NBR); -10 °C bis +140 °C (FKM)
Iekšējās daļas
Stainless steel
Korpuss, vārsta ligzda
Brass
Blīvējums
Perbunan (NBR) or FKM

Apraksts

Economy series available in three different versions: Directly operated, Combined operation, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	maks. darba spiediens bar	NW	Blīvēšanas materiāls	A mm	B mm	Konstrukcija
K- 07 30 23 66	G 1/8	20	02	FKM	54.0	40.0	2
K- 07 30 23 67	G 1/8	14	03	FKM	54.0	40.0	2
K- 07 30 23 68	G 1/4	10	03	FKM	54.0	40.0	2
K- 07 30 23 69	G 1/4	4	05	FKM	54.0	40.0	2