

K-MV 0 V 24 V DC 1

Normally open, pilot-operated, 24 V DC (direct current)



Aizsardzības veids
IP65 (with connector socket fitted)
Elektriskais pieslēgums
For connector socket Pg 9/Pg 11, acc. to ISO 4400
Vielas temperatūra
-10 °C to +90 °C (NBR); -10 °C bis +140 °C (FKM)
Iekšējās daļas
Stainless steel
Korpuss, vārsta ligzda
Brass
Blīvējums
Perbunan (NBR) or FKM

Apraksts

Economy series available in three different versions: Directly operated, Combined operation, Pilot-operated. For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītnes	maks. darba spiediens bar	min. ekspluatācijas spiediens bar	NW	Blīvēšanas materiāls	A mm	B mm	Konstrukcija
K- 07 30 23 93	G 3/8	16	0.20	13	NBR	54.0	60.0	4
K- 07 30 23 94	G 1/2	16	0.20	13	NBR	54.0	66.0	4
K- 07 30 23 95	G 3/4	16	0.20	19	NBR	54.0	104.0	6
K- 07 30 23 96	G 1	16	0.20	25	NBR	54.0	104.0	6
K- 07 30 23 97	G 1 1/4	10	0.20	35	NBR	54.0	144.0	6
K- 07 30 23 98	G 1 1/2	10	0.20	40	NBR	54.0	144.0	6
K- 07 30 23 99	G 2	10	0.20	50	NBR	54.0	172.0	6