

K-ENDPLATTEN V

End plate for HDM valve terminal

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba vides

Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens

Max. vacuum 10 bar (external pilots), 3 to 7 bar (internal pilots as standard)

Regulēšanas spiediens

3 - 7 bar

Temperatūras diapazons

-10 °C to +60 °C

Caurplūde

200 NL/min (Ø 4), 500 NL/min (Ø 6), 800 NL/min (Ø 8)

Aizsardzības veids

IP 65

Funkcija

Blind (terminates the system)

Jaudas patēriņš

0.6 W per pilot

Manuāla palīgvadība

Latching (bistable), Monostable (non-latching) version also available on request

Vadību skaits

Max. 16 (e.g. 16 spring return valves)

Apraksts

These compact valve terminals, with a maximum flow rate of 800 NL/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums

Funkcija

K- 07 15 22 50 Blind (terminates the system)