



Darba spiediens
 OR-AND: 1.5-8 bar, NOT: 0.4-6 bar, YES - MEMORY: 0.0-8 bar (pilot pressure from 1.5-8 bar)
 Temperatūras diapazons
 -10 °C to +60 °C
 Savienojums
 Push-in fitting for 4 mm pipe
 Atiestatišana
 OR - AND: by compressed air, MEMORY: by air, YES - NOT: by mechanical spring
 Caurpl_de nom.
 100 l/min
 Nominālais Ø
 2.7 mm
 Materiāls
 Technopolymer
 Aizbīdnis
 Aluminium
 Blīvējums
 NBR

Apraksts

Pneumatic logic elements are available with five different functions: OR, AND, NOT, YES, MEMORY. All elements have an adapter for the Q-rail (DIN EN 50022) integral with the body.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Nominālais Ø mm	Augstums mm	Funkcija	Garums mm
K- 07 15 13 77	2.7	40	OR	38.5
K- 07 15 13 78	2.7	40	AND	38.5
K- 07 15 13 79	2.7	40	NOT	55.2
K- 07 15 13 80	2.7	40	YES	55.2
K- 07 15 13 81	2.7	41	MEMORY	89.5