



Darba spiediens
OR-AND: 1.5-8 bar, NOT: 0.4-6 bar, YES - MEMORY: 0.0-8 bar (pilot pressure from 1.5-8 bar)
Temperatūras diapazons
-10 °C to +60 °C
Savienojums
Push-in fitting for 4 mm pipe
Atiestatīšana
OR - AND: by compressed air, MEMORY: by air, YES - NOT: by mechanical spring
Caurpl_de nom.
100 l/min
Nominālais Ø
2.7 mm
Materiāls
Technopolymer
Aizbīdnis
Aluminium
Blīvējums
NBR

Apraksts

Pneumatic logic elements are available with five different functions: OR, AND, NOT, YES, MEMORY. All elements have an adapter for the Q-rail (DIN EN 50022) integral with the body.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Nominālais Ø mm	Augstums mm	Funkcija	Garums mm
K- 07 15 13 77	2.7	40	OR	38.5
K- 07 15 13 78	2.7	40	AND	38.5
K- 07 15 13 79	2.7	40	NOT	55.2
K- 07 15 13 80	2.7	40	YES	55.2
K- 07 15 13 81	2.7	41	MEMORY	89.5