

# K-WV 3/2 5/2 NAMUR LB LF

3/2- and 5/2-way spool valves with NAMUR style interface and air spring



Darba vides  
Air, neutral gases, filtered  
Savienojums 1  
G 1/4"  
Darba spiediens  
1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)  
Ekspluatācijas temperatūra  
-20 °C to +50 °C  
Piegādes apjoms  
Plug connector PG 9, conversion plate, screws and seal  
Elektriskais pieslēgums  
Plug connector PG 9  
Jaudas patēriņš  
3 W=5 VA~  
Aizbīdnis  
Stainless steel  
Korpuss  
Anodised aluminium  
Blīvējums  
NBR  
Pieslēgums 3 + 5  
G 1/4"

## Apraksts

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Spriegums	Port 1	Pieslēgums 3 + 5	Caurpl_de nom. l/min	DN
K- 07 15 00 13	230 V, 50 Hz	G 1/4"	G 1/4"	1250	7
K- 07 15 00 14	24 V DC	G 1/4"	G 1/4"	1250	7