

K-WV 3/2 5/2 NAMUR LB LF

3/2- and 5/2-way spool valves with NAMUR style interface and air spring



Darba vides
Air, neutral gases, filtered
Savienojums 1
G 1/4"
Darba spiediens
1.5 to 10 bar (552.11 and 552.12); 2.5 to 10 bar (552.21 and 552.22)
Eksploatācijas temperatūra
-20 °C to +50 °C
Piegādes apjoms
Plug connector PG 9, conversion plate, screws and seal
Elektriskais pieslēgums
Plug connector PG 9
Jaudas patēriņš
3 W=5 VA~
Aizbīdnis
Stainless steel
Korpuss
Anodised aluminium
Blīvējums
NBR
Pieslēgums 3 + 5
G 1/4"

Apraksts

Pilot-operated 3/2- and 5/2-way spool valves with threaded ports and a NAMUR style interface with air purging function. By adding the conversion plate supplied with each valve, the device can be adapted to 3/2-way function.

Filter regulators are also available with bowl guard or metal bowl. Filter regulators are also available in lockable version. Please ask for more information.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Spriegums	Port 1	Pieslēgums 3 + 5	Caurpl_de nom. l/min	DN
K- 07 15 00 13	230 V, 50 Hz	G 1/4"	G 1/4"	1250	7
K- 07 15 00 14	24 V DC	G 1/4"	G 1/4"	1250	7