

# K-WV 3/2 LB NAMUR GETAUSCHT

**HANSA FLEX**

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

3/2-way spool valves with NAMUR style interface, NC, ports 1 and 3 or 2 and 3 swapped



Darba vides  
Air, neutral gases, filtered  
Darba spiediens  
1.5 to 10 bar  
Eksploatācijas temperatūra  
-20 °C to +70 °C  
Piegādes apjoms  
Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws  
Elektriskais pieslēgums  
Plug connector PG 9  
Jaudas patēriņš  
3 W=5 VA~  
Aizbīdnis  
Stainless steel  
Korpuss  
Aluminium, anodised  
Blīvējums  
NBR

## Apraksts

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Two or three-piece service units with excellent flow rates in modern design. &lt;br&gt;Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.&lt;br&gt;

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Spriegums	Caurpl_de nom. l/min	DN	Savienojums
K- 07 15 00 05	230 V, 50 Hz	1250	7	G 1/4"
K- 07 15 00 06	24 V DC	1250	7	G 1/4"