

K-WV 5/2 LOCHBILD NAMUR

5/2-way spool valves with NAMUR style interface

HANSA FLEX
OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA



Darba vides
Air, neutral gases, filtered
Darba spiediens
1.5 to 10 bar
Eksploatācijas temperatūra
-20 °C to +70 °C
Piegādes apjoms
Plug connector PG 9, 1 coding pin, 2 O-rings, 2 fixing screws
Elektriskais pieslēgums
Plug connector PG 9
Jaudas patēriņš
3 W=5 VA~
Aizbīdnis
Stainless steel
Korpuss
Aluminium, anodised
Blīvējums
NBR

Apraksts

3/2 and 5/2-way spool valves, monostable, with air purging function and pneumatic spring return. With latching manual operator and optional outgoing air restriction.

Two or three-piece service units with excellent flow rates in modern design.
Lockable diaphragm pressure regulator with secondary ventilation, oil can be filled without interrupting operation.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Spriegums	Caurpl_de nom. l/min	DN	Savienojums
K- 07 15 00 07	230 V, 50 Hz	1250	7	G 1/4"
K- 07 15 00 08	24 V DC	1250	7	G 1/4"