



Materiāls
GGG 40
Eksploatācijas spiediens
maks. 350 bar
Virsmas aizsardzība
cinkots

Produkts

| Apzīmējums | Vārsta urbums | A | C mm | D mm | E mm | F mm | G mm | G1 mm | H mm | I mm | L mm | M mm | Savienojums1,3 | Savienojums 3 | S |
|---------------------|---------------|------------------|---------|---------|---------|---------|---------|----------|---------|---------|---------|---------|----------------|---------------|---|
| HK GEH 38 C0830 GGG | C0830 | UNF 3/4" -16 | 60 | 65 | 29 | 30.0 | 29.5 | 15.0 | 15 | 7 | 7.5 | 44 | G 3/8" | G 3/8" | 0 |
| HK GEH 38 C1030 GGG | C1030 | UNF 7/8" -14 | 70 | 75 | 39 | 35.5 | 34.5 | 18.5 | 15 | 7 | 7.5 | 54 | G 3/8" | G 3/8" | 1 |
| HK GEH 12 C1230 GGG | C1230 | UNF 1,1/16" - 12 | 80 | 100 | 39 | 40.0 | 53.5 | 28.5 | 18 | 9 | 10.0 | 59 | G 3/4" | G 1/2" | 1 |