



Materiāls  
Tērauds S355J0 (Fe510C)  
Izmantošana  
Suitable for cylinder HK HFR 25

## Produkts

Apzīmējums	Ø AL mm	Ø F mm	Ø T mm	H mm	S mm	S1 mm	Z mm	Svars kg
HK CFHR2 0350 160 35	35	16.10	45	15	35	2	20	0.3
HK CFHR2 0400 200 40	40	20.25	50	18	40	2	20	0.5
HK CFHR2 0450 200 45	45	20.25	55	20	45	2	25	0.7
HK CFHR2 0500 250 49	50	25.25	60	22	49	2	25	0.8
HK CFHR2 0550 250 50	55	25.25	65	22	50	2	28	1.0
HK CFHR2 0600 250 47	60	25.25	70	22	47	2	23	1.1
HK CFHR2 0600 300 47	60	30.25	70	22	47	2	25	1.0
HK CFHR2 0630 250 53	63	25.25	73	23	53	2	30	1.4
HK CFHR2 0630 300 53	63	30.25	73	23	53	2	30	1.3
HK CFHR2 0650 250 50	65	25.25	75	22	50	2	28	1.4
HK CFHR2 0700 300 63	70	30.25	80	28	63	2	33	2.1
HK CFHR2 0750 300 60	75	30.25	90	25	60	2	35	2.4
HK CFHR2 0800 300 60	80	30.25	90	28	60	2	30	2.4
HK CFHR2 0800 400 60	80	40.25	90	28	60	2	32	2.0
HK CFHR2 0850 350 63	85	35.25	100	28	63	2	35	3.0
HK CFHR2 0900 350 63	90	35.25	105	28	63	2	35	3.4
HK CFHR2 0900 400 63	90	40.25	105	28	63	2	35	3.2
HK CFHR2 1000 300 63	100	30.25	115	28	63	2	33	4.4
HK CFHR2 1000 400 63	100	40.25	115	28	63	2	35	3.9
HK CFHR2 1100 400 75	110	40.25	125	35	75	2	40	5.9
HK CFHR2 1100 500 75	110	50.50	125	35	75	2	40	5.2
HK CFHR2 1200 500 95	120	50.50	140	45	95	2	50	9.1
HK CFHR2 1200 600 95	120	60.50	140	45	95	2	50	8.2
HK CFHR2 1250 500 95	125	50.50	145	45	95	2	50	9.9
HK CFHR2 1250 600 95	125	60.50	145	45	95	2	50	8.9
HK CFHR2 1400 601 10	140	60.50	160	50	110	2	60	13.6
HK CFHR2 1400 701 10	140	70.50	160	50	110	2	60	12.4
HK CFHR2 1500 701 30	150	70.50	170	55	130	2	75	17.8
HK CFHR2 1600 801 40	160	80.50	180	65	140	2	75	20.7