

Galvenais korpuss dubultas darbības hidrauliskajam cilindram 200 bar



Materiāls
Tērauda lējums UNI 5007-G26

Produkts

Apzīmējums	Ø A mm	Ø D mm	Ø S mm	F	L mm	L1 mm	Svars kg	piemērots blīvējumu komplekts
HK F 32 16	32	40	16	M 36x1.5	40	32	1.0	HK DSF 32 16
HK F 40 28	40	50	28	M 44x1.5	40	32	1.0	HK DSF 40 28
HK F 40 30	40	50	30	M 44x1.5	40	32	1.0	HK DSF 40 30
HK F 45 20	45	55	20	M 49x1.5	40	32	1.0	HK DSF 45 20
HK F 45 30	45	55	30	M 49x1.5	40	32	1.0	HK DSF 45 30
HK F 50 28	50	60	28	M 54x1.5	43	35	1.2	HK DSF 50 28
HK F 63 25	63	73	25	M 68x1.5	50	40	1.3	HK DSF 63 25
HK F 6336	63	73	36	M 68x1.5	50	40	1.2	HK DSF 63 36
HK F 63 45	63	73	45	M 68x1.5	50	40	1.3	HK DSF 63 45
HK F 125 80	125	145	80	M 130x2	92	80	5.0	HK DSF 125 80
HK F 140 100	140	160	100	M 145x2	92	80	4.0	HK DSF 140 100
HK F 150 100	150	170	100	M 155x2	102	90	4.5	HK DSF 150 100