



Darba spiediens

Max. 10 bar

Temperatūras diapazons

-10 °C to +60 °C (Ø 20 to Ø 63)

-10 °C to +80 °C (Ø 80 bis Ø 100)

Sākuma spiediens

0,6 bar (Ø 20 bis Ø 32), 0,4 bar (Ø 40 bis Ø 100)

Virzuļkāts

Stahl C45, hartverchromt

Caurule

Anodised aluminium jacket with T-slots

Virzulis

POM (Ø 20 to Ø 63); Aluminium (Ø 80 to Ø 100)

Darba vides

Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Blīvējums

NBR

Apraksts

New series acc. to ISO 21287 characterised by a very short and compact design. The standard type features a magnetic piston. Piston rod optionally with male or female thread.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta ārējā vītne
K- 07 15 08 09	20 mm	5	M5	M 8
K- 07 15 08 10	20 mm	10	M5	M 8
K- 07 15 08 11	20 mm	15	M5	M 8
K- 07 15 08 12	20 mm	20	M5	M 8
K- 07 15 08 13	20 mm	25	M5	M 8
K- 07 15 08 14	20 mm	30	M5	M 8
K- 07 15 08 15	20 mm	40	M5	M 8
K- 07 15 08 16	20 mm	50	M5	M 8
K- 07 15 08 17	20 mm	60	M5	M 8
K- 07 15 08 18	25 mm	5	M5	M 8
K- 07 15 08 19	25 mm	10	M5	M 8
K- 07 15 08 20	25 mm	15	M5	M 8
K- 07 15 08 21	25 mm	20	M5	M 8
K- 07 15 08 22	25 mm	25	M5	M 8
K- 07 15 08 23	25 mm	30	M5	M 8
K- 07 15 08 24	25 mm	40	M5	M 8
K- 07 15 08 25	25 mm	50	M5	M 8
K- 07 15 08 26	25 mm	60	M5	M 8
K- 07 15 08 27	32 mm	5	G 1/8"	M 10 x 1.25
K- 07 15 08 28	32 mm	10	G 1/8"	M 10 x 1.25
K- 07 15 08 29	32 mm	15	G 1/8"	M 10 x 1.25
K- 07 15 08 30	32 mm	20	G 1/8"	M 10 x 1.25
K- 07 15 08 31	32 mm	25	G 1/8"	M 10 x 1.25
K- 07 15 08 32	32 mm	30	G 1/8"	M 10 x 1.25
K- 07 15 08 33	32 mm	40	G 1/8"	M 10 x 1.25
K- 07 15 08 34	32 mm	50	G 1/8"	M 10 x 1.25
K- 07 15 08 35	32 mm	60	G 1/8"	M 10 x 1.25
K- 07 15 08 36	32 mm	80	G 1/8"	M 10 x 1.25
K- 07 15 08 37	40 mm	5	G 1/8"	M 10 x 1.25
K- 07 15 08 38	40 mm	10	G 1/8"	M 10 x 1.25
K- 07 15 08 39	40 mm	15	G 1/8"	M 10 x 1.25

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta ārējā vītne
K- 07 15 08 40	40 mm	20	G 1/8"	M 10 x 1.25
K- 07 15 08 41	40 mm	25	G 1/8"	M 10 x 1.25
K- 07 15 08 42	40 mm	30	G 1/8"	M 10 x 1.25
K- 07 15 08 43	40 mm	40	G 1/8"	M 10 x 1.25
K- 07 15 08 44	40 mm	50	G 1/8"	M 10 x 1.25
K- 07 15 08 45	40 mm	60	G 1/8"	M 10 x 1.25
K- 07 15 08 46	40 mm	80	G 1/8"	M 10 x 1.25
K- 07 15 08 47	50 mm	5	G 1/8"	M 12 x 1.25
K- 07 15 08 48	50 mm	10	G 1/8"	M 12 x 1.25
K- 07 15 08 49	50 mm	15	G 1/8"	M 12 x 1.25
K- 07 15 08 50	50 mm	20	G 1/8"	M 12 x 1.25
K- 07 15 08 51	50 mm	25	G 1/8"	M 12 x 1.25
K- 07 15 08 52	50 mm	30	G 1/8"	M 12 x 1.25
K- 07 15 08 53	50 mm	40	G 1/8"	M 12 x 1.25
K- 07 15 08 54	50 mm	50	G 1/8"	M 12 x 1.25
K- 07 15 08 55	50 mm	60	G 1/8"	M 12 x 1.25
K- 07 15 08 56	50 mm	80	G 1/8"	M 12 x 1.25
K- 07 15 08 57	63 mm	5	G 1/8"	M 12 x 1.25
K- 07 15 08 58	63 mm	10	G 1/8"	M 12 x 1.25
K- 07 15 08 59	63 mm	15	G 1/8"	M 12 x 1.25
K- 07 15 08 60	63 mm	20	G 1/8"	M 12 x 1.25
K- 07 15 08 61	63 mm	25	G 1/8"	M 12 x 1.25
K- 07 15 08 62	63 mm	30	G 1/8"	M 12 x 1.25
K- 07 15 08 63	63 mm	40	G 1/8"	M 12 x 1.25
K- 07 15 08 64	63 mm	50	G 1/8"	M 12 x 1.25
K- 07 15 08 65	63 mm	60	G 1/8"	M 12 x 1.25
K- 07 15 08 66	63 mm	80	G 1/8"	M 12 x 1.25
K- 07 15 08 67	80 mm	5	G 1/8"	M 16 x 1.5
K- 07 15 08 68	80 mm	10	G 1/8"	M 16 x 1.5
K- 07 15 08 69	80 mm	15	G 1/8"	M 16 x 1.5
K- 07 15 08 70	80 mm	20	G 1/8"	M 16 x 1.5
K- 07 15 08 71	80 mm	25	G 1/8"	M 16 x 1.5
K- 07 15 08 72	80 mm	30	G 1/8"	M 16 x 1.5
K- 07 15 08 73	80 mm	40	G 1/8"	M 16 x 1.5
K- 07 15 08 74	80 mm	50	G 1/8"	M 16 x 1.5
K- 07 15 08 75	80 mm	60	G 1/8"	M 16 x 1.5
K- 07 15 08 76	80 mm	80	G 1/8"	M 16 x 1.5
K- 07 15 07 99	100 mm	5	G 1/8"	M 16 x 1.5
K- 07 15 08 00	100 mm	10	G 1/8"	M 16 x 1.5
K- 07 15 08 01	100 mm	15	G 1/8"	M 16 x 1.5
K- 07 15 08 02	100 mm	20	G 1/8"	M 16 x 1.5
K- 07 15 08 03	100 mm	25	G 1/8"	M 16 x 1.5
K- 07 15 08 04	100 mm	30	G 1/8"	M 16 x 1.5
K- 07 15 08 05	100 mm	40	G 1/8"	M 16 x 1.5
K- 07 15 08 06	100 mm	50	G 1/8"	M 16 x 1.5
K- 07 15 08 07	100 mm	60	G 1/8"	M 16 x 1.5
K- 07 15 08 08	100 mm	80	G 1/8"	M 16 x 1.5