

K-KURZH ZYL DOPPELW ACP

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Short-stroke cylinders, double acting (magnetic, non-cushioned)



Darba vides

Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Eksploatācijas spiediens

maks. 10 bar

Temperatūras diapazons

-10 °C to +80 °C

Sākuma spiediens

0,6 bar (Ø 12 bis Ø 32), 0,4 bar (Ø 40 bis Ø 80)

Virzuļkāts

C45 steel, hard chrome-plated

Caurule

Aluminium alloy, anodised

Virzulis

Ø 12 to Ø 63 synthetic (acetal) resin, Ø 80 alu/PTFE

Blīvējums

NBR

Galvas diametrs

Ø 12 to Ø 25 painted brass, Ø 32 to Ø 80 aluminium

Apraksts

Suitable for installation in limited spaces, with magnet.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta iekšējā vītne
K- 07 15 11 31	12 mm	5	M5	M 3
K- 07 15 11 32	12 mm	10	M5	M 3
K- 07 15 11 33	12 mm	25	M5	M 3
K- 07 15 11 34	12 mm	30	M5	M 3
K- 07 15 11 35	12 mm	40	M5	M 3
K- 07 15 11 36	16 mm	5	M5	M 5
K- 07 15 11 37	16 mm	10	M5	M 5
K- 07 15 11 38	16 mm	25	M5	M 5
K- 07 15 11 39	16 mm	30	M5	M 5
K- 07 15 11 40	16 mm	40	M5	M 5
K- 07 15 11 41	20 mm	5	M5	M 5
K- 07 15 11 42	20 mm	10	M5	M 5
K- 07 15 11 43	20 mm	25	M5	M 5
K- 07 15 11 44	20 mm	30	M5	M 5
K- 07 15 11 45	20 mm	40	M5	M 5
K- 07 15 11 46	20 mm	50	M5	M 5
K- 07 15 11 47	25 mm	5	G 1/8"	M 5
K- 07 15 11 48	25 mm	10	G 1/8"	M 5
K- 07 15 11 49	25 mm	25	G 1/8"	M 5
K- 07 15 11 50	25 mm	30	G 1/8"	M 5
K- 07 15 11 51	25 mm	40	G 1/8"	M 5
K- 07 15 11 52	25 mm	50	G 1/8"	M 5
K- 07 15 11 53	32 mm	5	G 1/8"	M 6
K- 07 15 11 54	32 mm	10	G 1/8"	M 6
K- 07 15 11 55	32 mm	25	G 1/8"	M 6
K- 07 15 11 56	32 mm	30	G 1/8"	M 6
K- 07 15 11 57	32 mm	40	G 1/8"	M 6
K- 07 15 11 58	32 mm	50	G 1/8"	M 6
K- 07 15 11 59	40 mm	5	G 1/8"	M 6
K- 07 15 11 60	40 mm	10	G 1/8"	M 6
K- 07 15 11 61	40 mm	25	G 1/8"	M 6

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta iekšējā vītne
K- 07 15 11 62	40 mm	30	G 1/8"	M 6
K- 07 15 11 63	40 mm	40	G 1/8"	M 6
K- 07 15 11 64	40 mm	50	G 1/8"	M 6
K- 07 15 11 65	50 mm	5	G 1/8"	M 8
K- 07 15 11 66	50 mm	10	G 1/8"	M 8
K- 07 15 11 67	50 mm	25	G 1/8"	M 8
K- 07 15 11 68	50 mm	30	G 1/8"	M 8
K- 07 15 11 69	50 mm	40	G 1/8"	M 8
K- 07 15 11 70	50 mm	50	G 1/8"	M 8
K- 07 15 11 71	50 mm	70	G 1/8"	M 8
K- 07 15 11 72	63 mm	5	G 1/8"	M 8
K- 07 15 11 73	63 mm	10	G 1/8"	M 8
K- 07 15 11 74	63 mm	25	G 1/8"	M 8
K- 07 15 11 75	63 mm	30	G 1/8"	M 8
K- 07 15 11 76	63 mm	40	G 1/8"	M 8
K- 07 15 11 77	63 mm	50	G 1/8"	M 8
K- 07 15 11 78	63 mm	70	G 1/8"	M 8
K- 07 15 11 79	80 mm	5	G 1/4"	M 10
K- 07 15 11 80	80 mm	10	G 1/4"	M 10
K- 07 15 11 81	80 mm	25	G 1/4"	M 10
K- 07 15 11 82	80 mm	30	G 1/4"	M 10
K- 07 15 11 83	80 mm	40	G 1/4"	M 10
K- 07 15 11 84	80 mm	50	G 1/4"	M 10
K- 07 15 11 85	80 mm	70	G 1/4"	M 10
K- 07 15 11 86	80 mm	100	G 1/4"	M 10