

# K-RUNDZYLINDER DOPP O D

**HANSA FLEX**

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Miniature cylinders, double acting (magnetic, non-cushioned)



Darba vides  
Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens  
Max. 10 bar

Temperatūras diapazons  
-10 °C to +80 °C

Sākuma spiediens  
0,8 bar (Ø 8 bis Ø 12), 0,6 bar (Ø 16 bis Ø 25)

Virzuļkāts  
Stahl C45, hartverchromt

Caurule  
Stainless steel 1.4301

Uzstādīšana  
Flanged joint between stainless steel barrel and heads

Virzulis  
Synthetic (acetal) resin

Blīvējums  
NBR

## Apraksts

Single and double-acting cylinders, with magnetic piston.

## Norādot

Citi dati pieejami pēc pieprasījuma.

## Produkts

| Apzīmējums     | Ø virzulim | Gājiens<br>mm | Savienojums | Virzuļkāta vītne |
|----------------|------------|---------------|-------------|------------------|
| K- 07 15 16 67 | 8 mm       | 10            | M5          | M 4              |
| K- 07 15 16 68 | 8 mm       | 25            | M5          | M 4              |
| K- 07 15 16 69 | 8 mm       | 50            | M5          | M 4              |
| K- 07 15 16 70 | 8 mm       | 80            | M5          | M 4              |
| K- 07 15 16 71 | 8 mm       | 100           | M5          | M 4              |
| K- 07 15 16 72 | 10 mm      | 10            | M5          | M 4              |
| K- 07 15 16 73 | 10 mm      | 25            | M5          | M 4              |
| K- 07 15 16 74 | 10 mm      | 50            | M5          | M 4              |
| K- 07 15 16 75 | 10 mm      | 80            | M5          | M 4              |
| K- 07 15 16 76 | 10 mm      | 100           | M5          | M 4              |
| K- 07 15 16 77 | 12 mm      | 10            | M5          | M 6              |
| K- 07 15 16 78 | 12 mm      | 25            | M5          | M 6              |
| K- 07 15 16 79 | 12 mm      | 50            | M5          | M 6              |
| K- 07 15 16 80 | 12 mm      | 80            | M5          | M 6              |
| K- 07 15 16 81 | 12 mm      | 100           | M5          | M 6              |
| K- 07 15 16 82 | 12 mm      | 125           | M5          | M 6              |
| K- 07 15 16 83 | 12 mm      | 160           | M5          | M 6              |
| K- 07 15 16 84 | 12 mm      | 200           | M5          | M 6              |
| K- 07 15 16 85 | 16 mm      | 10            | M5          | M 6              |
| K- 07 15 16 86 | 16 mm      | 25            | M5          | M 6              |
| K- 07 15 16 87 | 16 mm      | 50            | M5          | M 6              |
| K- 07 15 16 88 | 16 mm      | 80            | M5          | M 6              |
| K- 07 15 16 89 | 16 mm      | 100           | M5          | M 6              |
| K- 07 15 16 90 | 16 mm      | 125           | M5          | M 6              |
| K- 07 15 16 91 | 16 mm      | 160           | M5          | M 6              |
| K- 07 15 16 92 | 16 mm      | 200           | M5          | M 6              |
| K- 07 15 16 93 | 20 mm      | 10            | G 1/8"      | M 8              |
| K- 07 15 16 94 | 20 mm      | 25            | G 1/8"      | M 8              |
| K- 07 15 16 95 | 20 mm      | 50            | G 1/8"      | M 8              |
| K- 07 15 16 96 | 20 mm      | 80            | G 1/8"      | M 8              |
| K- 07 15 16 97 | 20 mm      | 100           | G 1/8"      | M 8              |

| Apzīmējums     | Ø virzulim | Gājiens<br>mm | Savienojums | Virzuļkāta vitne |
|----------------|------------|---------------|-------------|------------------|
| K- 07 15 16 98 | 20 mm      | 125           | G 1/8"      | M 8              |
| K- 07 15 16 99 | 20 mm      | 160           | G 1/8"      | M 8              |
| K- 07 15 17 00 | 20 mm      | 200           | G 1/8"      | M 8              |
| K- 07 15 17 01 | 20 mm      | 250           | G 1/8"      | M 8              |
| K- 07 15 17 02 | 25 mm      | 10            | G 1/8"      | M 10 x 1.25      |
| K- 07 15 17 03 | 25 mm      | 25            | G 1/8"      | M 10 x 1.25      |
| K- 07 15 17 04 | 25 mm      | 50            | G 1/8"      | M 10 x 1.25      |
| K- 07 15 17 05 | 25 mm      | 80            | G 1/8"      | M 10 x 1.25      |
| K- 07 15 17 06 | 25 mm      | 100           | G 1/8"      | M 10 x 1.25      |
| K- 07 15 17 07 | 25 mm      | 125           | G 1/8"      | M 10 x 1.25      |
| K- 07 15 17 08 | 25 mm      | 160           | G 1/8"      | M 10 x 1.25      |
| K- 07 15 17 09 | 25 mm      | 200           | G 1/8"      | M 10 x 1.25      |
| K- 07 15 17 10 | 25 mm      | 250           | G 1/8"      | M 10 x 1.25      |