

K-RUNDZYLINDER DOPP O D

Miniature cylinders, double acting (magnetic, non-cushioned)



Darba vides

Filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens

Max. 10 bar

Temperatūras diapazons

-10 °C to +80 °C

Sākuma spiediens

0,8 bar (Ø 8 bis Ø 12), 0,6 bar (Ø 16 bis Ø 25)

Virzuļkāts

Stahl C45, hartverchromt

Caurule

Stainless steel 1.4301

Uzstādīšana

Flanged joint between stainless steel barrel and heads

Virzulis

Synthetic (acetal) resin

Blīvējums

NBR

Apraksts

Single and double-acting cylinders, with magnetic piston.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta vītne
K- 07 15 16 67	8 mm	10	M5	M 4
K- 07 15 16 68	8 mm	25	M5	M 4
K- 07 15 16 69	8 mm	50	M5	M 4
K- 07 15 16 70	8 mm	80	M5	M 4
K- 07 15 16 71	8 mm	100	M5	M 4
K- 07 15 16 72	10 mm	10	M5	M 4
K- 07 15 16 73	10 mm	25	M5	M 4
K- 07 15 16 74	10 mm	50	M5	M 4
K- 07 15 16 75	10 mm	80	M5	M 4
K- 07 15 16 76	10 mm	100	M5	M 4
K- 07 15 16 77	12 mm	10	M5	M 6
K- 07 15 16 78	12 mm	25	M5	M 6
K- 07 15 16 79	12 mm	50	M5	M 6
K- 07 15 16 80	12 mm	80	M5	M 6
K- 07 15 16 81	12 mm	100	M5	M 6
K- 07 15 16 82	12 mm	125	M5	M 6
K- 07 15 16 83	12 mm	160	M5	M 6
K- 07 15 16 84	12 mm	200	M5	M 6
K- 07 15 16 85	16 mm	10	M5	M 6
K- 07 15 16 86	16 mm	25	M5	M 6
K- 07 15 16 87	16 mm	50	M5	M 6
K- 07 15 16 88	16 mm	80	M5	M 6
K- 07 15 16 89	16 mm	100	M5	M 6
K- 07 15 16 90	16 mm	125	M5	M 6
K- 07 15 16 91	16 mm	160	M5	M 6
K- 07 15 16 92	16 mm	200	M5	M 6
K- 07 15 16 93	20 mm	10	G 1/8"	M 8
K- 07 15 16 94	20 mm	25	G 1/8"	M 8
K- 07 15 16 95	20 mm	50	G 1/8"	M 8
K- 07 15 16 96	20 mm	80	G 1/8"	M 8
K- 07 15 16 97	20 mm	100	G 1/8"	M 8

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta vitne
K- 07 15 16 98	20 mm	125	G 1/8"	M 8
K- 07 15 16 99	20 mm	160	G 1/8"	M 8
K- 07 15 17 00	20 mm	200	G 1/8"	M 8
K- 07 15 17 01	20 mm	250	G 1/8"	M 8
K- 07 15 17 02	25 mm	10	G 1/8"	M 10 x 1.25
K- 07 15 17 03	25 mm	25	G 1/8"	M 10 x 1.25
K- 07 15 17 04	25 mm	50	G 1/8"	M 10 x 1.25
K- 07 15 17 05	25 mm	80	G 1/8"	M 10 x 1.25
K- 07 15 17 06	25 mm	100	G 1/8"	M 10 x 1.25
K- 07 15 17 07	25 mm	125	G 1/8"	M 10 x 1.25
K- 07 15 17 08	25 mm	160	G 1/8"	M 10 x 1.25
K- 07 15 17 09	25 mm	200	G 1/8"	M 10 x 1.25
K- 07 15 17 10	25 mm	250	G 1/8"	M 10 x 1.25