

K-RUNDZYLINDER DOPP O D 1

HANSA FLEX

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Round cylinders, double acting (magnetic, non-cushioned)



Darba vides
Filtered (50 µm), unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens
Max. 10 bar

Temperatūras diapazons
-10 °C to +80 °C

Sākuma spiediens
0,4 bar (Ø 32 und Ø 40), 0,3 bar (Ø 50)

Virzuļkāts
Stahl C45, hartverchromt

Caurule
Anodised aluminium

Uzstādišana
Screwed joint between stainless steel barrel and heads

Virzulis
Technopolymer

Blīvējums
NBR

Apraksts

Version with magnetic piston

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta vītne
K- 07 15 17 29	32 mm	25	G 1/8"	M 10 x 1.25
K- 07 15 17 30	32 mm	50	G 1/8"	M 10 x 1.25
K- 07 15 17 31	32 mm	80	G 1/8"	M 10 x 1.25
K- 07 15 17 32	32 mm	100	G 1/8"	M 10 x 1.25
K- 07 15 17 33	32 mm	125	G 1/8"	M 10 x 1.25
K- 07 15 17 34	32 mm	160	G 1/8"	M 10 x 1.25
K- 07 15 17 35	32 mm	200	G 1/8"	M 10 x 1.25
K- 07 15 17 36	32 mm	250	G 1/8"	M 10 x 1.25
K- 07 15 17 37	32 mm	320	G 1/8"	M 10 x 1.25
K- 07 15 17 38	32 mm	400	G 1/8"	M 10 x 1.25
K- 07 15 17 39	32 mm	500	G 1/8"	M 10 x 1.25
K- 07 15 17 40	40 mm	25	G 1/4"	M 12 x 1.25
K- 07 15 17 41	40 mm	50	G 1/4"	M 12 x 1.25
K- 07 15 17 42	40 mm	80	G 1/4"	M 12 x 1.25
K- 07 15 17 43	40 mm	100	G 1/4"	M 12 x 1.25
K- 07 15 17 44	40 mm	125	G 1/4"	M 12 x 1.25
K- 07 15 17 45	40 mm	160	G 1/4"	M 12 x 1.25
K- 07 15 17 46	40 mm	200	G 1/4"	M 12 x 1.25
K- 07 15 17 47	40 mm	250	G 1/4"	M 12 x 1.25
K- 07 15 17 48	40 mm	320	G 1/4"	M 12 x 1.25
K- 07 15 17 49	40 mm	400	G 1/4"	M 12 x 1.25
K- 07 15 17 50	40 mm	500	G 1/4"	M 12 x 1.25
K- 07 15 17 51	50 mm	25	G 1/4"	M 16 x 1.5
K- 07 15 17 52	50 mm	50	G 1/4"	M 16 x 1.5
K- 07 15 17 53	50 mm	80	G 1/4"	M 16 x 1.5
K- 07 15 17 54	50 mm	100	G 1/4"	M 16 x 1.5
K- 07 15 17 55	50 mm	125	G 1/4"	M 16 x 1.5
K- 07 15 17 56	50 mm	160	G 1/4"	M 16 x 1.5
K- 07 15 17 57	50 mm	200	G 1/4"	M 16 x 1.5
K- 07 15 17 58	50 mm	250	G 1/4"	M 16 x 1.5

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta vītne
K- 07 15 17 59	50 mm	320	G 1/4"	M 16 x 1.5
K- 07 15 17 60	50 mm	400	G 1/4"	M 16 x 1.5
K- 07 15 17 61	50 mm	500	G 1/4"	M 16 x 1.5