

# K-RUNDZYLINDER DOPP O D 1

**HANSA FLEX**

OFICIĀLĀ LATVIJAS PĀRSTĀVNICĪBA

Round cylinders, double acting (magnetic, non-cushioned)



Darba vides  
Filtered (50 µm), unlubricated or lubricated compressed air. If lubrication is used, it must be continuous.

Darba spiediens  
Max. 10 bar

Temperatūras diapazons  
-10 °C to +80 °C

Sākuma spiediens  
0,4 bar (Ø 32 und Ø 40), 0,3 bar (Ø 50)

Virzuļkāts  
Stahl C45, hartverchromt

Caurule  
Anodised aluminium

Uzstādišana  
Screwed joint between stainless steel barrel and heads

Virzulis  
Technopolymer

Blīvējums  
NBR

## Apraksts

Version with magnetic piston

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta vītne
K- 07 15 17 29	32 mm	25	G 1/8"	M 10 x 1.25
K- 07 15 17 30	32 mm	50	G 1/8"	M 10 x 1.25
K- 07 15 17 31	32 mm	80	G 1/8"	M 10 x 1.25
K- 07 15 17 32	32 mm	100	G 1/8"	M 10 x 1.25
K- 07 15 17 33	32 mm	125	G 1/8"	M 10 x 1.25
K- 07 15 17 34	32 mm	160	G 1/8"	M 10 x 1.25
K- 07 15 17 35	32 mm	200	G 1/8"	M 10 x 1.25
K- 07 15 17 36	32 mm	250	G 1/8"	M 10 x 1.25
K- 07 15 17 37	32 mm	320	G 1/8"	M 10 x 1.25
K- 07 15 17 38	32 mm	400	G 1/8"	M 10 x 1.25
K- 07 15 17 39	32 mm	500	G 1/8"	M 10 x 1.25
K- 07 15 17 40	40 mm	25	G 1/4"	M 12 x 1.25
K- 07 15 17 41	40 mm	50	G 1/4"	M 12 x 1.25
K- 07 15 17 42	40 mm	80	G 1/4"	M 12 x 1.25
K- 07 15 17 43	40 mm	100	G 1/4"	M 12 x 1.25
K- 07 15 17 44	40 mm	125	G 1/4"	M 12 x 1.25
K- 07 15 17 45	40 mm	160	G 1/4"	M 12 x 1.25
K- 07 15 17 46	40 mm	200	G 1/4"	M 12 x 1.25
K- 07 15 17 47	40 mm	250	G 1/4"	M 12 x 1.25
K- 07 15 17 48	40 mm	320	G 1/4"	M 12 x 1.25
K- 07 15 17 49	40 mm	400	G 1/4"	M 12 x 1.25
K- 07 15 17 50	40 mm	500	G 1/4"	M 12 x 1.25
K- 07 15 17 51	50 mm	25	G 1/4"	M 16 x 1.5
K- 07 15 17 52	50 mm	50	G 1/4"	M 16 x 1.5
K- 07 15 17 53	50 mm	80	G 1/4"	M 16 x 1.5
K- 07 15 17 54	50 mm	100	G 1/4"	M 16 x 1.5
K- 07 15 17 55	50 mm	125	G 1/4"	M 16 x 1.5
K- 07 15 17 56	50 mm	160	G 1/4"	M 16 x 1.5
K- 07 15 17 57	50 mm	200	G 1/4"	M 16 x 1.5
K- 07 15 17 58	50 mm	250	G 1/4"	M 16 x 1.5

Apzīmējums	Ø virzulim	Gājiens mm	Savienojums	Virzuļkāta vītne
K- 07 15 17 59	50 mm	320	G 1/4"	M 16 x 1.5
K- 07 15 17 60	50 mm	400	G 1/4"	M 16 x 1.5
K- 07 15 17 61	50 mm	500	G 1/4"	M 16 x 1.5