



Modelis
Miksts blīvējums
Standarts
DIN 3869
Materiāls
FPM (Viton)

Produkts

Apzīmējums	vītnei	Ø Da mm	Ø di mm	S mm
WD 8-1 V	M 8 x 1	9.9	6.5	1.0
WD 10-1 R1/8 V	M 10 x 1	11.9	8.4	1.0
WD 12-1.5 V	M 12 x 1.5	14.4	9.8	1.5
WD 14-1.5 R1/4 V	M 14 x 1.5	16.5	11.6	1.5
WD 16-1.5 V	M 16 x 1.5	18.9	13.8	1.5
WD R3/8 V	-	18.9	14.7	1.5
WD 18-1.5 V	M 18 x 1.5	20.9	15.7	1.5
WD 20-1.5 V	M 20 x 1.5	22.9	17.8	1.5
WD R1/2 V	-	23.9	18.5	1.5
WD 22-1.5 V	M 22 x 1.5	24.3	19.6	1.5
WD 26-27- R3/4 V	M 26 x 1.5	29.2	23.9	1.5
WD 33-2 R1 V	M 33 x 2	35.7	29.7	2.0
WD 42-2 R1 1/4 V	M 42 x 2	45.8	38.8	2.0
WD 48-2 R1 1/2 V	M 48 x 2	50.7	44.7	2.0
WD R 2 V	-	66.0	56.0	4.0