

OR 80° Shore NBR

Apļa šķērsriezuma gredzens, 80SH NBR



Modelis
Apļa šķērsriezuma gredzens
Temperatūra maks.
110 °C
Temperatūra min.
-30 °C
Materiāls
NBR, Šora cietība 80

Produkts

Apzīmējums	d1 mm	d2 mm	s mm
OR 5-1.5 N80	5.00	8.00	1.50
OR 8-1.9 N80	8.00	11.80	1.90
OR 8.73-1.78 N80	8.73	12.29	1.78
OR 12-2 N80	12.00	16.00	2.00
OR 12.42-1.78 N80	12.42	15.98	1.78
OR 13.94-2.62 N80	13.94	19.18	2.62
OR 14-2.5 N80	14.00	19.00	2.50
OR 16-3 N80	16.00	22.00	3.00
OR 18.3-3.6 N80	18.30	25.50	3.60
OR 19.8-3.6 N80	19.80	27.00	3.60
OR 21.3-3.6 N80	21.30	28.50	3.60
OR 21.89-2.62 N80	21.89	27.13	2.62
OR 23-2 N80	23.00	27.00	2.00
OR 23-3.6 N80	23.00	30.20	3.60
OR 24.6-3.6 N80	24.60	31.80	3.60
OR 25.12-1.78 N80	25.12	28.68	1.78
OR 26.2-3.6 N80	26.20	33.40	3.60
OR 27.8-3.6 N80	27.80	35.00	3.60
OR 28.17-3.53 N80	28.17	35.23	3.53
OR 29-3 N80	29.00	35.00	3.00
OR 29-3.5 N80	29.00	36.00	3.50
OR 29.3-3.6 N80	29.30	36.50	3.60
OR 31.42-2.62 N80	31.42	36.66	2.62
OR 32-3.5 N80	32.00	39.00	3.50
OR 32.5-3.6 N80	32.50	39.70	3.60
OR 34.1-3.6 N80	34.10	41.30	3.60
OR 34.59-2.62 N80	34.59	39.83	2.62
OR 35.6-3.6 N80	35.60	42.80	3.60
OR 37.3-3.6 N80	37.30	44.50	3.60
OR 39.5-2.5 N80	39.50	44.50	2.50
OR 40-3 N80	40.00	46.00	3.00
OR 40.64-5.34 N80	40.64	51.32	5.34
OR 42.86-3.53 N80	42.86	49.92	3.53
OR 46-3 N80	46.00	52.00	3.00
OR 49.2-3.53 N80	49.20	56.26	3.53
OR 50-3 N80	50.00	56.00	3.00
OR 50.17-5.34 N80	50.17	60.85	5.34
OR 53.57-3.53 N80	53.57	60.63	3.53
OR 55-3 N80	55.00	61.00	3.00
OR 55.25-2.62 N80	55.25	60.49	2.62
OR 58.74-3.53 N80	58.74	65.80	3.53

Apzīmējums	d1 mm	d2 mm	s mm
OR 60-3 N80	60.00	66.00	3.00
OR 65.1-3.53 N80	65.10	72.16	3.53
OR 67-3 N80	67.00	73.00	3.00
OR 68-6 N80	68.00	80.00	6.00
OR 69.44-3.53 N80	69.44	76.50	3.53
OR 72.62-3.53 N80	72.62	79.68	3.53
OR 75.79-3.53 N80	75.79	82.85	3.53
OR 81.92-5.34 N80	81.92	92.60	5.34
OR 88-6 N80	88.00	100.00	6.00
OR 89.69-5.34 N80	89.69	100.37	5.34
OR 97.79-5.34 N80	97.79	108.47	5.34
OR 107.54-3.53 N80	107.54	114.60	3.53
OR 113.89-3.53 N80	113.89	120.95	3.53
OR 116.84-5.34 N80	116.84	127.52	5.34
OR 117.07-3.53 N80	117.07	124.13	3.53
OR 126.37-5.34 N80	126.37	137.05	5.34
OR 126.37-7 N80	126.37	140.37	7.00
OR 132.72-7 N80	132.72	146.72	7.00
OR 133.35-5.34 N80	133.35	144.03	5.34
OR 139.07-7 N80	139.07	153.07	7.00
OR 139.29-3.53 N80	139.29	146.35	3.53
OR 142.24-5.34 N80	142.24	152.92	5.34
OR 142.24-7 N80	142.24	156.24	7.00
OR 145.42-5.34 N80	145.42	156.10	5.34
OR 148.82-3.53 N80	148.82	155.88	3.53
OR 151.77-5.34 N80	151.77	162.45	5.34
OR 151.77-7 N80	151.77	165.77	7.00
OR 158.12-7 N80	158.12	172.12	7.00
OR 164.47-5.34 N80	164.47	175.15	5.34
OR 170.82-5.34 N80	170.82	181.50	5.34
OR 177.17-7 N80	177.17	191.17	7.00
OR 183.52-5.34 N80	183.52	194.20	5.34
OR 189.87-5.34 N80	189.87	200.55	5.34
OR 190.09-3.53 N80	190.09	197.15	3.53
OR 202.57-7 N80	202.57	216.57	7.00
OR 240.67-7 N80	240.67	254.67	7.00
OR 291.47-7 N80	291.47	305.47	7.00