

OR 80° Shore NBR

Apļa šķērsriezuma gredzens, 80SH NBR



Modelis
Apļa šķērsriezuma gredzens
Temperatūra maks.
110 °C
Temperatūra min.
-30 °C
Materiāls
NBR, Šora cietība 80

Produkts

| Apzīmējums | d1 mm | d2 mm | s mm |
|-------------------|----------|----------|---------|
| OR 5-1.5 N80 | 5.00 | 8.00 | 1.50 |
| OR 8-1.9 N80 | 8.00 | 11.80 | 1.90 |
| OR 8.73-1.78 N80 | 8.73 | 12.29 | 1.78 |
| OR 12-2 N80 | 12.00 | 16.00 | 2.00 |
| OR 12.42-1.78 N80 | 12.42 | 15.98 | 1.78 |
| OR 13.94-2.62 N80 | 13.94 | 19.18 | 2.62 |
| OR 14-2.5 N80 | 14.00 | 19.00 | 2.50 |
| OR 16-3 N80 | 16.00 | 22.00 | 3.00 |
| OR 18.3-3.6 N80 | 18.30 | 25.50 | 3.60 |
| OR 19.8-3.6 N80 | 19.80 | 27.00 | 3.60 |
| OR 21.3-3.6 N80 | 21.30 | 28.50 | 3.60 |
| OR 21.89-2.62 N80 | 21.89 | 27.13 | 2.62 |
| OR 23-2 N80 | 23.00 | 27.00 | 2.00 |
| OR 23-3.6 N80 | 23.00 | 30.20 | 3.60 |
| OR 24.6-3.6 N80 | 24.60 | 31.80 | 3.60 |
| OR 25.12-1.78 N80 | 25.12 | 28.68 | 1.78 |
| OR 26.2-3.6 N80 | 26.20 | 33.40 | 3.60 |
| OR 27.8-3.6 N80 | 27.80 | 35.00 | 3.60 |
| OR 28.17-3.53 N80 | 28.17 | 35.23 | 3.53 |
| OR 29-3 N80 | 29.00 | 35.00 | 3.00 |
| OR 29-3.5 N80 | 29.00 | 36.00 | 3.50 |
| OR 29.3-3.6 N80 | 29.30 | 36.50 | 3.60 |
| OR 31.42-2.62 N80 | 31.42 | 36.66 | 2.62 |
| OR 32-3.5 N80 | 32.00 | 39.00 | 3.50 |
| OR 32.5-3.6 N80 | 32.50 | 39.70 | 3.60 |
| OR 34.1-3.6 N80 | 34.10 | 41.30 | 3.60 |
| OR 34.59-2.62 N80 | 34.59 | 39.83 | 2.62 |
| OR 35.6-3.6 N80 | 35.60 | 42.80 | 3.60 |
| OR 37.3-3.6 N80 | 37.30 | 44.50 | 3.60 |
| OR 39.5-2.5 N80 | 39.50 | 44.50 | 2.50 |
| OR 40-3 N80 | 40.00 | 46.00 | 3.00 |
| OR 40.64-5.34 N80 | 40.64 | 51.32 | 5.34 |
| OR 42.86-3.53 N80 | 42.86 | 49.92 | 3.53 |
| OR 46-3 N80 | 46.00 | 52.00 | 3.00 |
| OR 49.2-3.53 N80 | 49.20 | 56.26 | 3.53 |
| OR 50-3 N80 | 50.00 | 56.00 | 3.00 |
| OR 50.17-5.34 N80 | 50.17 | 60.85 | 5.34 |
| OR 53.57-3.53 N80 | 53.57 | 60.63 | 3.53 |
| OR 55-3 N80 | 55.00 | 61.00 | 3.00 |
| OR 55.25-2.62 N80 | 55.25 | 60.49 | 2.62 |
| OR 58.74-3.53 N80 | 58.74 | 65.80 | 3.53 |

| Apzīmējums | d1 mm | d2 mm | s mm |
|--------------------|----------|----------|---------|
| OR 60-3 N80 | 60.00 | 66.00 | 3.00 |
| OR 65.1-3.53 N80 | 65.10 | 72.16 | 3.53 |
| OR 67-3 N80 | 67.00 | 73.00 | 3.00 |
| OR 68-6 N80 | 68.00 | 80.00 | 6.00 |
| OR 69.44-3.53 N80 | 69.44 | 76.50 | 3.53 |
| OR 72.62-3.53 N80 | 72.62 | 79.68 | 3.53 |
| OR 75.79-3.53 N80 | 75.79 | 82.85 | 3.53 |
| OR 81.92-5.34 N80 | 81.92 | 92.60 | 5.34 |
| OR 88-6 N80 | 88.00 | 100.00 | 6.00 |
| OR 89.69-5.34 N80 | 89.69 | 100.37 | 5.34 |
| OR 97.79-5.34 N80 | 97.79 | 108.47 | 5.34 |
| OR 107.54-3.53 N80 | 107.54 | 114.60 | 3.53 |
| OR 113.89-3.53 N80 | 113.89 | 120.95 | 3.53 |
| OR 116.84-5.34 N80 | 116.84 | 127.52 | 5.34 |
| OR 117.07-3.53 N80 | 117.07 | 124.13 | 3.53 |
| OR 126.37-5.34 N80 | 126.37 | 137.05 | 5.34 |
| OR 126.37-7 N80 | 126.37 | 140.37 | 7.00 |
| OR 132.72-7 N80 | 132.72 | 146.72 | 7.00 |
| OR 133.35-5.34 N80 | 133.35 | 144.03 | 5.34 |
| OR 139.07-7 N80 | 139.07 | 153.07 | 7.00 |
| OR 139.29-3.53 N80 | 139.29 | 146.35 | 3.53 |
| OR 142.24-5.34 N80 | 142.24 | 152.92 | 5.34 |
| OR 142.24-7 N80 | 142.24 | 156.24 | 7.00 |
| OR 145.42-5.34 N80 | 145.42 | 156.10 | 5.34 |
| OR 148.82-3.53 N80 | 148.82 | 155.88 | 3.53 |
| OR 151.77-5.34 N80 | 151.77 | 162.45 | 5.34 |
| OR 151.77-7 N80 | 151.77 | 165.77 | 7.00 |
| OR 158.12-7 N80 | 158.12 | 172.12 | 7.00 |
| OR 164.47-5.34 N80 | 164.47 | 175.15 | 5.34 |
| OR 170.82-5.34 N80 | 170.82 | 181.50 | 5.34 |
| OR 177.17-7 N80 | 177.17 | 191.17 | 7.00 |
| OR 183.52-5.34 N80 | 183.52 | 194.20 | 5.34 |
| OR 189.87-5.34 N80 | 189.87 | 200.55 | 5.34 |
| OR 190.09-3.53 N80 | 190.09 | 197.15 | 3.53 |
| OR 202.57-7 N80 | 202.57 | 216.57 | 7.00 |
| OR 240.67-7 N80 | 240.67 | 254.67 | 7.00 |
| OR 291.47-7 N80 | 291.47 | 305.47 | 7.00 |