



Ieejas spiediens
Max. 15 bar
Savienojums
G 1/4 internal / external
Materiāls
Misiņš

Apraksts

Industry, trade and repair shops often require working pressures of 15 bar or less. These pressure reducing valves, which are screwed directly onto the tool, enable the actually necessary working pressure to be set.
Benefits: Significantly reduced risk of accidents, Longer tool life with fewer malfunctions, Lower noise levels at the workplace.

Norādot

Citi dati pieejami pēc pieprasījuma.

Produkts

| Apzīmējums | Iestatītais spiediens | maks.: caurplūde l/min | A mm | B | SW mm | Ø C mm |
|-------------------|-----------------------|---------------------------|---------|--------|----------|-----------|
| K- 07 25 19 31 02 | 02 | 300 | 34.0 | 9.0 mm | 17 | 17.0 |
| K- 07 25 02 00 03 | 03 | 360 | 34.0 | 9.0 mm | 17 | 17.0 |
| K- 07 25 02 01 04 | 04 | 380 | 34.0 | 9.0 mm | 17 | 17.0 |
| K- 07 25 02 02 05 | 05 | 390 | 34.0 | 9.0 mm | 17 | 17.0 |
| K- 07 25 02 03 06 | 06 | 405 | 34.0 | 9.0 mm | 17 | 17.0 |
| K- 07 25 19 32 07 | 07 | 415 | 34.0 | 9.0 mm | 17 | 17.0 |
| K- 07 25 19 33 08 | 08 | 420 | 34.0 | 9.0 mm | 17 | 17.0 |