

K-INLINE-DRG AG IG 0

SEKUNDAERENTLU

Inline pressure regulators, non-self-relieving



Ekspluatācijas spiediens
max. 18 bar
Temperatūras diapazons
0 °C to +60 °C
Spiediena pielāgšana
± 0.3 bar at 10 l/min
citas daļas
Brass, NBR, stainless steel
Korpuss
Zinc

Apraksts

This single-acting diaphragm regulator can be installed in any pneumatic system. Since the pressure is preset in the factory and cannot be altered, the product is also tamper-proof. We recommend mounting the regulator directly on the tool to make sure the correct pressure is applied. In this case, the tool is never stressed by the higher pressure of the supply system and is protected against pressure fluctuations in hoses, pipes, etc. Energy efficiency and economic efficiency can be achieved by using an inline pressure regulator.

Norādīt

Citi dati pieejami pēc pieprasījuma.

Produkts

Apzīmējums	Vītne	Priekšiestatītais darba spiediens	A mm	B	SW mm
K- 07 25 02 75	G 1/4	1 bar	34.0	52.0 mm	17
K- 07 25 02 76	G 1/4	2 bar	34.0	52.0 mm	17
K- 07 25 02 77	G 1/4	3 bar	34.0	52.0 mm	17
K- 07 25 02 78	G 1/4	4 bar	34.0	52.0 mm	17
K- 07 25 02 79	G 1/4	5 bar	34.0	52.0 mm	17
K- 07 25 02 80	G 1/4	6 bar	34.0	52.0 mm	17
K- 07 25 02 81	G 1/4	6,5 bar	34.0	52.0 mm	17
K- 07 25 02 82	G 1/4	7 bar	34.0	52.0 mm	17