

# K-INLINE-DRG IG M

## SEKUNDAERENTLUEFT

Inline pressure regulators, 2 x female thread, self-relieving



Ekspluatācijas spiediens  
Max. 25 bar  
Temperatūras diapazons  
0 °C to +80 °C  
citas daļas  
Stainless steel, nitrile rubber, brass  
Korpuss  
Aluminium

## Apraksts

The majority of pneumatic tools are connected directly to the compressed air supply by means of a quick disconnect coupling, in other words they tend to be supplied with a higher pressure than is actually required. Which increases consumption and leads to tool overload. Added safety is provided by the automatic self-relieving function. If the tool is disconnected from the hose, it continues to work for a short period, even though it has been switched off, owing to the residual pressure that is present on the tool side. &lt;br&gt;Inadvertent operation of the tool can thus lead to serious injuries to the user (tackers or nail drivers can fire up to another ten shots). &lt;br&gt;This effect can be prevented by using the inline pressure regulators, which have a preset pressure determined by the application, thereby achieving energy efficiency and economy.

## Norādīt

Citi dati pieejami pēc pieprasījuma.

## Produkts

Apzīmējums	Vītnes	Priekšiestatītais darba spiediens	Caurplūde	A mm	SW mm
K- 07 25 02 83	G 1/4	2 bar	600 - 800 l/min	56.6	16
K- 07 25 02 84	G 1/4	3 bar	600 - 800 l/min	56.6	16
K- 07 25 02 85	G 1/4	4 bar	600 - 800 l/min	56.6	16
K- 07 25 02 86	G 1/4	5 bar	600 - 800 l/min	56.6	16
K- 07 25 02 87	G 1/4	6 bar	600 - 800 l/min	56.6	16
K- 07 25 02 88	G 1/4	8 bar	600 - 800 l/min	56.6	16
K- 07 25 02 89	G 3/8	2 bar	2000 l/min	63.0	22
K- 07 25 02 90	G 3/8	4 bar	2000 l/min	63.0	22
K- 07 25 02 91	G 3/8	6 bar	2000 l/min	63.0	22
K- 07 25 02 92	G 3/8	8 bar	2000 l/min	63.0	22
K- 07 25 02 93	G 1/2	2 bar	3000 l/min	67.5	27
K- 07 25 02 94	G 1/2	4 bar	3000 l/min	67.5	27
K- 07 25 02 95	G 1/2	6 bar	3000 l/min	67.5	27
K- 07 25 02 96	G 1/2	8 bar	3000 l/min	67.5	27